

HGA RACK 2U PRO (SX 3080)

PEM Rack 19 inch Hydrogen generator
with ZeroAir integrated

The HydroGen series **HGA RACK 19" 2U PRO** is able to generate up to 600 cc/min Hydrogen with purity better than 99.99999% and pressure up to 16 bar (232 PSI). An AirGen output can deliver hydrocarbon free pure Air with a flow up to 2000 cc/min. The **HGA RACK 19 inch 2U PRO** includes an electrolytic cell with polymeric membrane (PEM) using distilled water. The two-column PSA drying system with automatic regeneration ensures the maximum grade of hydrogen purity, and is completely maintenance-free.

The **HGA RACK 19 inch 2U PRO** is the ideal Hydrogen and Air Generator for all GC-FID detectors. The on-board CPU constantly control the operating parameters to guarantee full safety. The touch-screen LCD interface provides simple and user-friendly management of all functions on the unit.

Main Applications

- Carrier gas for GC and GC-MS
- GC-FID / GC-NPD / GC-FPD
- THA

Main Advantages

- ✓ Quick installation
- ✓ Easy use
- ✓ Hydrogen flow rate up to 600 cc/min
- ✓ ZeroAir flow rate up to 2000 cc/min
- ✓ Pressure up to 16 bar (232 psi)
- ✓ Hydrogen purity: 99.99999%
- ✓ THC: < 0.1 ppm
- ✓ RS 485 and USB as standard
- ✓ LAN optional
- ✓ Dryer with no maintenance
- ✓ Reduced foot print: 19 inch rack 2U
- ✓ High pressure GLS electronically controlled (patented)





Specifications

Models: HGA 2U PRO	100	160	250	350	600
General data					
Electrolytic cell	PEM technology				
Drying system	PSA (Pressure Swing Adsorption)				
H2 purity	>99.99999% ¹				
Outlet pressure	12 bars (174 psi) / 16 bars (232 psi) (optional)				
H2 flow-rate cc/min (Max)	100	160	250	350	600
Dimensions	Standard 19 inch 2U RACK (48 cm deep)				
Net weight (no water in tank)	15.5 kg				
Communication					
RS485/USB	Standard				
LAN	Optional				
Software functions					
Parallel mode	Ready on board				
Automatic tank refill	Standard				
Water					
Quality	Deionized, ASTM II, <0.1uS				
Supply pressure (min, Max)	-0.2 bars (1.4 psi), 0.5 bar (7.25 psi)				
Internal tank capacity	0.3 l				
Electrical data					
Type of connection	IEC 320-C13				
Power supply voltage	100-240 Vac 50/60 Hz				
Installed power (Max)	350W				500W
Fuse rating (5x 20 mm)	4A 250VAC				
Connections					
Hydrogen outlet	1/8" compression fitting				
Water (inlet, drain)	Quick release push-in fitting				
ZeroAir section					
Inlet pressure (Max)	8 bars (116 psi)				
THC (Inlet Air)	100ppm				
Outlet flow rate (max)	2000 cc/min				
Outlet pressure (max)	Inlet pressure – 0.5 bars (8 psi) at maximum flow				
THC (ZeroAir Outlet)	<0.1ppm				
Inlet, Outlet ports	1/8" BSPP female				

¹ Referred to O₂ - DewPoint < -75°C

DASTEC S.R.L.

Representantes / Distribuidores Exclusivos

Argentina

Tel: (+54 11) 5352 2500

Email: info@dastecsr.com.ar

Web: www.dastecsr.com.ar

Uruguay www.dastecsr.com.uy

Paraguay www.dastecsr.com.py



LNI Swissgas

www.lni-swissgas.eu

Ordering codes

Gas Generators

6920.17.010

6920.17.016

6920.17.025

6920.17.035

6920.17.060

Consumable

6930.00.091

HGA 2U PRO 100

HGA 2U PRO 160

HGA 2U PRO 250

HGA 2U PRO 350

HGA 2U PRO 600

Deionizer water filter

LNI Swissgas Srl

Registered office: Via Sassoferato 1, 20135 Milano MI

Logistics centre: Via E. Mattei 9, 35038 Torreglia PD